



INDUSTRIAL HOSE | DISPENSING HOSE

Fueling the future.



GOODYEAR

DEF DISPENSING HOSE



Urea tanks will be standard equipment for most new diesel trucks, buses, cars and sport utility vehicles (SUVs) manufactured in the United States after Jan. 1, 2010. Goodyear Engineered Products DEF dispensing hose provides a dispensing solution for your diesel operations.

GOODYEAR
ENGINEERED PRODUCTS

adelaide belt & hose

42 Scotland Road, Mile End SA 5031
Email: sales@abhose.com.au
www.beltandhose.com.au

Phone: 08 8234 1155

Fax 08 8234 2255



AIR &
MULTIPURPOSE
*General Purpose
Heavy Duty
Push-on*

CHEMICAL
TRANSFER

CLEANING
EQUIPMENT

FOOD
*Transfer
Washdown*

MARINE

MATERIAL
HANDLING
*Abrasives
Bulk Transfer
Cement & Concrete*

MINING

PETROLEUM
*Aircraft Fueling
Dispensing
Dock
Transfer*

SPRAY

STEAM

VACUUM

VEYANCE

WATER
*Discharge
Suction & Discharge
Washdown*

WELDING

COUPLING
SYSTEMS

DEF DISPENSING HOSE



Product Specifications

APPLICATION: Urea tanks will be standard equipment for most new diesel trucks, buses, cars and sport utility vehicles (SUVs) manufactured in the United States after Jan. 1, 2010. An automotive grade of urea will be injected into the vehicles' exhaust stream to "scrub" nitrogen oxide (NOx) from the diesel exhaust.

NOx, a major air pollutant, contributes to smog, which causes asthma and respiratory and heart diseases. The system, urea SCR or "urea-based selective catalytic reduction," is the only technology available that can remove enough NOx from diesel exhaust to comply with strict new limits imposed by the U.S. Environmental Protection Agency (EPA).

Goodyear Engineered Products DEF Dispensing Hose is specifically designed to convey the aqueous urea solution 32 (AUS 32), a clear 32.5% nitrogen solution of high-purity urea in demineralized water.

CONSTRUCTION TUBE: Specially formulated low-extraction EPDM, peroxide cured

COVER: Specially formulated low-extraction EPDM, peroxide cured

REINFORCEMENT: Polyester braid

TEMPERATURE: -40°F to 257°F (-40°C to 125°C)

PACKAGING: Bulk, coupled assemblies

BRANDING: Example: Goodyear® DEF Dispensing Hose 3/4" (19.1mm) Made in EU

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure

DEF DISPENSING HOSE

SIZE	INSIDE DIAMETER		OUTSIDE DIAMETER		WEIGHT		BURST	
	in.	mm.	in.	mm.	lbs/ft	kg/m	psi	bar
3/4"	0.75	19.1	1.13	28.8	.30	.457	1211	83.5

For more information, call 1-800-235-4632 (US), 1-888-275-4397 (Canada), or visit www.goodyear.com/hose.

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company. Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates. ©2009 Veyance Technologies, Inc. All Rights Reserved.



09GHOS026 - 06/09

goodyear.com

Aftermarket Parts - Automotive, Conveyor Belt - Heavyweight and Lightweight, Government, Heavy Duty, Home and Garden, Hydraulics, Industrial Hose, Power Transmission Products, Powersports, Rubber Track, Seawing Offshore Oil Hose

